150 W HALOGEN LIGHT SOURCE F. O. HEAD LIGHTS



30801 GIMA HALOGEN LIGHT SOURCE 150 Watt

Compact, lightweight, powerful light source for endoscopic use. A low noise fan positioned behind the halogen bulb provides the necessary cooling inside the metallic structure of the light source. A variable-intensity regulator enables selection 50 to 150 W. User manual in GB, ES, FR, IT, GR, PT.

| GIMA code | CONNECTORS FOR GIMA LIGHT SOURCE TO DIFFERENT CABLES |
|--------------|--|
| 30810 | STORZ cable connector |
| 30811 | WOLF cable connector |
| 30812 | OLYMPUS cable connector |
| 30815 | PENTAX cable connector |
| 30816 | FUJINON cable connector |
| 30808 | Spare lamp 150W |

LUT cables Dimension: 21x20x h 11 cm


Max power absoption: 170 Watt Two protection fuses: 1.6 A.T. Power supply: 230V-50 Hz Norms: IEC 601-1 - 93/42/EEC (Class: I - Type: BF)

Made in Italy: GIMA S.p.a.

TECHNICAL SPECIFICATIONS Input for GIMA, SCHOLLY and

spot Ø 10 mm.

Diameter focus:



An exceptionally bright headlight with an illumination head for coaxial, shadow-free illumination of the viewing area.



- 30850 WIDA FIBRE OPTIC HEAD LIGHT
- 30854 WIDA PLUS FIBRE OPTIC HEAD LIGHT

fibre optic cable complete with head light system

WIDA illumination systems are available in two versions: one with simple headband and standard illumination head, the other with professional headband, easily adjustable, and thin head. Both include F.O. cable with adaptor (30830) for connection to GIMA light source (30801).


Here below are available connectors to other light sources. Light beam can be focused through

a focusing ring.

• 30852 FOCUS DEVICE for 30850 (since lot 14 - may 2012)

It reduces light in a very luminous





Illumination axis adiustable over

a wide range

30850

LED LIGHT SOURCE


• 27544 LED LIGHT SOURCE

Cold white light (5,500 °K, 200 lumen) for endoscopy use. It can be connected to endoscopes without need of F.O. cable. Handle connect directly to rigid endoscopes LCD display: (Storz connection).

12 8x6 4 cm



SURGICAL FIBRE OPTIC LIGHT CABLES AND ADAPTORS





- LIGHT SOURCE ADAPTORS to connect GIMA F.O. cables to light sources • 30830 GIMA light source adaptor - 30831 STORZ - AESCULAP-MARTIN light source adaptor • 30832 WOLF - HENKE SASS - DYONICS -MEDICON - COMEG light source adaptor 30833 OLYMPUS light source ad. • 30834 ACMI light source adaptor • 30835 HEINE light source adaptor

 - 30836 FUJINON light source adaptor
 30837 PENTAX light source adaptor
 - **2** ENDOSCOPE ADAPTORS on the cables
- to connect endoscopes to GIMA F.O. cables
 - 30840 ENDO STORZ adaptor
 - 30841 ENDO WOLF adaptor • 30842 ENDO ACM, **OLYMPUS-STRYKER** adaptor

- 30817 FIBRE OPTIC CABLE 3.5 x 1,800 mm
- 30818 FIBRE OPTIC CABLE 4.8 x 1,800 mm
- 30822 FIBRE OPTIC CABLE 3.5 x 2.300 mm
- 30823 FIBRE OPTIC CABLE 4.8 x 2,300 mm
- 30826 FIBRE OPTIC CABLE 4.8 x 3,000 mm

High transmission surgical light cables, armoured but highly flexible with unique features:

- no burn outs
- strain relieved and protected by silicone hose
- steam autoclavable with warranty (12 months)
- light source end temperature resistant up to 300°C
- kink resistant
- no electrical interferences with endoscopic surgery units
- surgical stainless steel end fittings resist wear and corrosion
- stainless steel adaptors enables our cables to be used with other manufacturers halogen light sources/instruments
- 29975 FIBRE OPTIC CLAMP

SENDOSCOPE ADAPTORS - on the endoscope to connect endoscopes to GIMA F.O. cables

- 30844 STORZ/LUT ENDOSCOPE ADAPTORS
- 30845 WOLF ENDOSCOPE ADAPTORS

